



STAINLESS STEEL CABLE TIES & MARKERS



ROLLER BALL TYPE STAINLESS STEEL CABLE TIES

MATERIAL : STAINLESS STEEL GRADE 316/304

Features :

- This roller ball design tie are self locking and very easy to install.
- Fixing can be done by hand, tool & both.

Specification :

- Min. loop tensile strength - 4.6mm width (44.5kg) 100 lbs
- Min. loop tensile strength - 7.9mm width (113.6kg) 250 lbs

Operating Temperature :

-80°C to +150°C (Coated)
-80°C to +538°C (UnCoated)

Applications :

Construction, Automobile, Offshore, Petro-Chemical Industries, Fire Protection, Aerospace, Flame Proof Installation etc.

Length (mm)	Width (mm)	Max Bundle Dia. (mm)	Product Code
100	4.6	16	HH100
150	4.6	32	HH150
200	4.6	50	HH200
360	4.6	101	HH360
520	4.6	152	HH520
680	4.6	203	HH680
840	4.6	254	HH840
1000	4.6	298	HH1000
200	7.9	50	HH200 H
360	7.9	101	HH360 H
520	7.9	152	HH520 H
680	7.9	203	HH680 H
840	7.9	254	HH840 H
1000	7.9	298	HH1000 H

For coated version add Suffix 'CT' to product code
(For example : CTHH100 for 100mm length)

RELEASABLE TYPE STAINLESS STEEL CABLE TIES

MATERIAL : STAINLESS STEEL GRADE 316/304

Features :

- This ties have greater flexibility as it can Fasten-Unfasten-Refasten as per usage.
- Coated ties are used for added resistance to corrosion and weathering effect.

Operating Temperature :

-80°C to +150°C (Coated)



Length (mm)	Width (mm)	Max Bundle Dia. (mm)	Product Code
150	5	36	HRT1505
230	5	60	HRT2305
330	5	95	HRT3305
450	5	130	HRT4505
150	10	36	HRT1501
230	10	60	HRT2301
330	10	95	HRT3301
450	10	130	HRT4501

For coated version add Suffix 'CT' to product code
(For example : CTHRT 1505 for 150mm length)

LADDER TYPE STAINLESS STEEL CABLE TIES

MATERIAL : STAINLESS STEEL GRADE 316/304
FINISH : COATED & UNCOATED

Features :

- Easy application due to self locking construction.
- Fixing can be done by hand, tool & both.
- Coated ties are used for added resistant to corrosion and weathering effect.

Specification:

- Min. loop tensile strength - 7mm width (44.5kg) 100 lbs
- Min. loop tensile strength - 12mm width (113.6kg) 250 lbs

Operating Temperature :

- 80°C to +150°C (Coated)
- 80°C to +538°C (UnCoated)

Applications :

Construction, Automobile, Offshore, Petroleum & Chemical Industries, Fire Protection, Aerospace etc.

Length (mm)	Width (mm)	Max Bundle Dia. (mm)	Product Code
200	7	50	HSS2007
225	7	60	HSS2257
250	7	70	HSS2507
300	7	80	HSS3007
360	7	105	HSS3607
450	7	115	HSS4507
600	7	140	HSS6007
610	7	150	HSS6107
750	7	200	HSS7507
1000	7	300	HSS10007
200	12	50	HSS20012
225	12	60	HSS22512
250	12	70	HSS25012
300	12	80	HSS30012
360	12	105	HSS36012
450	12	115	HSS45012
600	12	140	HSS60012
640	12	150	HSS64012
750	12	200	HSS75012
1000	12	300	HSS100012

For coated version add Suffix 'CT' to product code
(For example : CTHSS2007 for 200mm length)

STEEL MARKING SYSTEM

MATERIAL : STAINLESS STEEL GRADE 316/304

This range of Stainless Steel Marketing System is available for effortless and permanent identification of cable assemblies or ducting system, Also can be used in harsh environment. This system can be applied with Rollerball or Ladder Type S. S. Ties.

Description (mm)	Dimension (Length x Width) mm	Product Code
Embossable Tag	63 x 34	HDET - 63
Embossable Tag	51 x 19	HDET - 51
Embossable Tag	89 x 19	HDET - 89
Carrier 6	92.5 x 8	HIT - 6
Carrier 6	130.6 x 8	HIT - 10
Carrier 6	187.7 x 8	HIT - 16
Alphabets	9 x 8	A.....Z
Numbers	9 x 8	0.....9
Symbols	9 x 8	-, +, ~, /, Blank, Earth

