


ELPS ACCESSORIES

CONDUCTORS

Bare Copper Tape

High conductivity Cu Tape to BS - 1432 - C101/C103

Conductor (A x B) mm	Product Code
20 x 1.5	HCT - 2015
25 x 1.5	HCT - 2515
25 x 3	HCT - 253
25 x 4	HCT - 254
25 x 6	HCT - 256
40 x 6	HCT - 406
50 x 3	HCT - 503
50 x 6	HCT - 506



FLEXIBLE COPPER BRAIDS

High conductivity Copper


Wire to BS - 4109 - C101

Suitable for Earth Bonding.

Also supplied as Standard Drilled & Pre-Cut Bonds.

Customer specific sizes & types of braid can be manufactured on order.

Size mm ²	Overall Nominal Equivalent Size mm (AxB)	Product Code
8.75	Bare Braid 15 x 1.4	HBB - 151
34.7	Bare Braid 25 x 3.5	HBB - 253
34.7	Tinned Braid 25 x 3.5	HTB - 253




CONDUCTORS - SOLID / STRANDED

Bare Solid Circular Conductor

Cu to BS - 1433 - C101 / 103

Al to BS 2898 - 1350

Conductor	Dia. (D) mm	Cross Section area mm ²	Product Code
Copper	8	50.27	HBSC - 8C
Aluminium	8	50.27	HBSC - 8A



Bare Stranded Copper Conductor

Soft Drawn Cu Conductor to BS - 6360

Size mm ²	Stranding No. / mm	Product Code
6	7 / 1.04	HBCU - 6
16	7 / 1.70	HBCU - 16
25	7 / 2.14	HBCU - 25
35	7 / 2.52	HBCU - 35
50	19 / 1.75	HBCU - 50
70	19 / 2.14	HBCU - 70
95	19 / 2.52	HBCU - 95

