



## LED Highbays

Designed to provide drastic reductions in both energy consumption and maintenance requirements, RELITE LED High Bay Series provide uniform light with no dark patches and good colour rendering. Available models 100W -200W

### Product Features

- Powerful LED light source with a unique design
- Extensive Options can replace all types of Standard MH Highbays
- Aluminum Diffuser
- Shatter Proof Perspex Lens
- High Thermal Conductivity, Low Luminous Decay, Pure Colours & No Heavy Shade
- The unique design of Radiator fuses with the Lamp Box perfectly hence diffuses the heat conduction efficiently which reduces the temperature of inside lamp

### Applications

Perfect fit for Industrial Usage, Warehouse & Super Markets, Workshops, Factories, Warehouses, Highway, toll Stations, Gas Stations, Malls, Exhibition Halls, Stadiums & other vast areas.

www.alfaelec.ae



LED High Bays



Reflector Highbay-SMD

**200W RL-HB200**

SKU: 9511 6000K White

Sensor Compatible: **Yes**  
Voltage/Frequency: **AC-100-240V,50/60Hz**  
Luminous Flux: **16000lm**  
LED Type: **SMD**  
CRI: **>80**

PF: **>0.9**  
Beam Angle: **120°**  
Body Type: **Aluminium**  
IP Rating: **IP-65**  
Dimension: **498 x 335mm**



Reflector Highbay-SMD

**150W RL-HB150**

SKU: 9513 6000K White

Sensor Compatible: **Yes**  
Voltage/Frequency: **AC-100-240V,50/60Hz**  
Luminous Flux: **12000lm**  
LED Type: **SMD**  
CRI: **>80**

PF: **>0.9**  
Beam Angle: **120°**  
Body Type: **Aluminium**  
IP Rating: **IP-65**  
Dimension: **498 x 335mm**



## Reflector Highbay-SMD

100W RL-HB100

SKU: 9514 6000K White

Sensor Compatible:	Yes	PF:	>0.9
Voltage/Frequency:	AC-100-240V,50/60Hz	Beam Angle:	120°
Luminous Flux:	8000lm	Body Type:	Aluminium
LED Type:	SMD	IP Rating:	IP-65
CRI:	>70	Dimension:	397 x 190mm

Live . Light . Life |   CE/EMC