



# Industrial Fan Series



01 Strong & Durable Motor

Large Air Volume & low noise 02

03 Pass 5000 hours aging test

04 Suitable for heat-stroke prevention & cooling down in many industrial & commercial places.






## INDUSTRIAL FAN SERIES



2 aluminum blades



Pure Copper Motor



1.8mm wire diameter and 10mm wire spacing, 12 pcs., clip type fastener grill



1.3m adjustable pole



51cm Wall-mounted pipe



5.5/7kg cross rubber base



Wide Angle Wind 80°



Rotation L/R



High velocity Strong wind



8 speeds Options



Model No.: FL-500-E(20")  
FL-600-E(24")  
FL-650-E(26")  
FL-750-E(30")

Model No.: FLW-500-E(20")  
FLW-600-E(24")  
FLW-650-E(26")  
FLW-750-E(30")

### Technical parameters

| Size      | Voltage/V   | Phase | HZ    | Power/W | r/min | M3/min | Db(A) | Dimension A(cm) | Dimension B(cm) | Dimension C(cm) | Dimension D(cm) | Dimension E(cm) |
|-----------|-------------|-------|-------|---------|-------|--------|-------|-----------------|-----------------|-----------------|-----------------|-----------------|
| 20"/500mm | 110/220/380 | 1/3   | 50/60 | 100-135 | 1350  | 160    | 73    | 57              | 177             | 55/65           | 50              | 53              |
| 24"/600mm | 110/220/380 | 1/3   | 50/60 | 130-170 | 1350  | 175    | 76    | 66              | 182             | 55/65           | 50              | 53              |
| 26"/650mm | 110/220/380 | 1/3   | 50/60 | 140-180 | 1350  | 180    | 80    | 71              | 184             | 55/65           | 50              | 53              |
| 30"/750mm | 110/220/380 | 1/3   | 50/60 | 160-200 | 1350  | 250    | 86    | 81              | 189             | 55/65           | 50              | 53              |

7

Remarks: The parameters above are for reference only, please subject to real specification as negotiation.