

LED SLIM SURFACE ROUND DOWNLIGHT

Product Features

Thermal Conductive Plastic Coated
 Aluminum Housing
 V-0 Flame rating
 Integrated design, built-in Driver
 Class II Electrical protection
 L70 - 30,000Hrs
 CE , CB, ROHS ErP certified product

Application

Offices
 Classrooms
 Hall ways
 Luxurious Hotels
 Supermarkets

Advantages

80% Energy Saving
 Environmentally Safe
 Less Heat produced
 Innovative ,
 Easy installation and long Life



TECHNICAL DATA

Product Code	: RLD 30W-SR
Power	: 24W
Voltage	: 220-240V AC
Luminous Flux	: 1920 Lm
Efficacy	: 80 Lm/W
Energy efficiency	: A+
Net weight	: 0.465 Kg
CRI	: > 80
Beam angle	: 140°
Operating temperature	: -20 °C to + 40 °C
Storage temperature	: Up to 50°C
Material	: Aluminium & Plastic body
CCT	: 3000K / 4000 / 6500K
IP	: 44
Dimmable	: No
Life Time	: 30,000Hrs
Cover	: Frosted Diffuser
Finishing color	: White
Mounting	: Surface
Size in mm (LxWxH)	: 300X39

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

