

LED SLIM SURFACE SQUARE DOWNLIGHT

Product Features

Thermal Conductive Plastic Coated Aluminum Housing, V-0 Flame rating, Integrated design, built-in Driver, Class II Electrical protection, L70-30,000Hrs, CE , CB, ROHS ErP certified product

Application

Offices
Classrooms
Hall ways
Luxurious Hotels
Supermarkets

Advantages

80% Energy Saving
Environmentally Safe
Less Heat produced
Innovative ,
Easy installation and long Life



TECHNICAL DATA

Product Code	: RL30W-RS
Power	: 24W
Voltage	: 220-240V AC
Luminous Flux	: 1920 Lm
Efficacy	: 80 Lm/W
Energy efficiency	: A+
Net weight	: 0.46 Kg
CRI	: > 80
Beam angle	: 140°
Operating temperature	: -20 °C to + 40 °C
Storage temperature	: Up to 50°C
Material	: Aluminium & Plastic body
CCT	: 3000K / 4000 / 6500K
IP	: 44
Dimmable	: No
Life Time	: 30,000Hrs
Cover	: Frosted Diffuser
Finishing color	: White
Mounting	: Recessed
Size in mm (LxWxH)	: 300X300X12

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

