

**LED SLIM SURFACE ROUND DOWNLIGHT**

**Product Features**

Thermal Conductive Plastic Coated  
 Aluminum Housing  
 V-0 Flame rating  
 Integrated design, built-in Driver  
 Class II Electrical protection  
 L70 - 30,000Hrs  
 CE , CB, ROHS ErP certified product

**Application**

Offices  
 Classrooms  
 Hall ways  
 Luxurious Hotels  
 Supermarkets

**Advantages**

80% Energy Saving  
 Environmentally Safe  
 Less Heat produced  
 Innovative ,  
 Easy installation and long Life



**TECHNICAL DATA**

Product Code	: RLD 20W-SR
Power	: 18W
Voltage	: 220-240V AC
Luminous Flux	: 1450 Lm
Efficacy	: 80 Lm/W
Energy efficiency	: A+
Net weight	: 0.465 Kg
CRI	: > 80
Beam angle	: 140°
Operating temperature	: -20 °C to + 40 °C
Storage temperature	: Up to 50°C
Material	: Aluminium & Plastic body
CCT	: 3000K / 4000 / 6500K
IP	: 44
Dimmable	: No
Life Time	: 30,000Hrs
Cover	: Frosted Diffuser
Finishing color	: White
Mounting	: Surface
Size in mm (LxWxH)	: 300X39

**LUMINOUS INTENSITY DISTRIBUTION DIAGRAM**

