

8" LED RECESSED FIXED DOWNLIGHT

Product Features

Die Cast Aluminum Housing
 COB - Chip On Board
 Class II Electrical protection
 L70 - 30,000Hrs
 CE , CB, ROHS ErP certified product

Application

Offices
 Classrooms
 Hall ways
 Luxurious Hotels
 Supermarkets

Advantages

80% Energy Saving
 Environmentally Safe
 Less Heat produced
 Innovative , Easy
 installation and long Life



TECHNICAL DATA

Product Code	: RL-20-6F	RL-30-8F
Power	: 20W	30W
Voltage	: 220-240V AC	220-240V AC
Luminous Flux	: 1820 Lm	2730 Lm
Efficacy	: 91 Lm/W	91 Lm/W
Energy efficiency	: A+	A+
Net weight	: 0.515 Kg	0.96 Kg
CRI	: > 80	> 80
Beam angle	: 140°	140°
Operating temperature	: -10 °C to + 40 °C	-10 °C to + 40 °C
Storage temperature	: Up to 50°C	Up to 50°C
Material	: Die Cast Aluminium	Die Cast Aluminium
CCT	: 3000K / 6500K	3000K / 6500K
IP	: 20	20
Dimmable	: No	No
Life Time	: 30,000Hrs	30,000Hrs
Cover	: Clear Glass	Clear Glass
Finishing color	: White	White
Mounting	: Recessed	Recessed
Size in mm (LxWxH)	: 165X55	225X75

