





<sup>®</sup> REXANS



**Flexible  
PVC Coated  
Galvanized  
Tubes**



MADE IN INDIA



# REXANS<sup>®</sup>

Flexible PVC Coated Galvanized Tubes



- Product** : PVC Coated Steel Flexible Conduit
- Construction** : Helically Wound Square lock Flexible Conduit overaheath with PVC.  
The Conduit Will be Uniform in diameter through our it's length.  
The internal surface of the conduit will be free from burrs & sharp edges.
- Colour** : Self
- PVC Coating** : Black/Grey PVC Also available in LFHSUV resistant

## SPECIFICATION :

- High Mechanical Strength
- Low Smoke Density
- Temperature Range  
15°C to +70°C
- IP Rating: IP40 & IP54

Size	Internal Diameter (MM)	External Diameter (MM)	Min. Bend Radius (MM)	Coil Packing (Mtr)
16 MM	13	16	30	20
20 MM	14	20	30	20
25 MM	21	25	43	20
32 MM	28	32	50	15
40 MM	35	40	57	10
50 MM	45	50	70	10

## APPLICATION

- Public & Commercial buildings
- Outdoor installations
- Used as mechanical protection for insulated electrical cables and wires that are functional in normal atmospheric temperature
- Under floor applications for computer/floor boxes
- Used for connecting machines to controls
- Elevators, Metro Stations , CCTV Camera etc.
- Most suitable for tight-spot installation and in places where certain water tightness is required.

**Raw Material** : Pre-galvanised Steel Sheet Z80-120Gsm weight of surface area as basic core material Virgin PVC soil granules

**Marking & Packing** : Flexible Conduit are Packed in Strong box

**Cutting** : We recommend use of fine tooth 32tpi. Hacksaw, short conduit length can be readily contractor packed.

**Standard & Approvals** : All Standard Quality Conduits are manufactured in accordance to IS-3480. BS-731 part 1 Assistance Has been derived from the following while preparing this standard.